



FLECK® 3 00

3 VALVE CONTROL SYSTEM

54" x 14" x 14" E, T, L, V, M, L

MADE IN THE
USA
OF FOREIGN & DOMESTIC PARTS



FEATURES/BENEFITS

- Lead-free brass valve body for superior strength and durability
- Continuous service flow rate of 250 GPM with a backwash of 100 GPM
- Backwash capability accommodates softener tanks up to 63" and filter up to 42" in diameter
- Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system
- Designed for single or multiple tank systems

- Environmental protective cover for water resistance, corrosion resistance, and UV stability
- Time-tested, hydraulically-balanced piston for service and regeneration
- Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

OPTIONS

- Filter or softener control valves
- Downflow co-current or upflow counter-current regeneration
- No hard water bypass piston
- Brine cam auxiliary switch
- Electromechanical timer auxiliary switch
- Treated water regeneration
- Versatile top or side mount
- Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration

NXT- Network controller uses on-board communication capabilities to link multiple valves (via off-the-shelf CAT3, CAT5, or better cables) for system types 4,5,6,7,9, and 14

XT- Offers a two-line, 16 character LCD backlit display for easy entering of master and user programming as well as view of diagnostics

Electromechanical Timer- Simple to adjust and easy to service with quick access to all internal components



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 61 Section 8 Material Safety Only.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



Restriction of Hazardous Substance Compliant

VALVE SPECIFICATIONS

Valve Material	Lead-free brass*
Inlet/Outlet	3" NPTF/BSPF
Cycles	3 or 5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi drop	250 GPM (56.8 m³/h)
Peak 25 psi drop	325 GPM (73.8 m³/h)
Cv flow at 1 psi drop	65
Max. Backwash 25 psi drop	100 GPM (22.7 m³/h)

REGENERATION

Downflow/Upflow	Both
Adjustable Cycles	Yes
Time Available	
Electromechanical:	0 - 164 min/regeneration
NXT:	0 - 240 min/cycle
XT:	0 - 240 min/cycle

METER INFORMATION

Meter Accuracy	
3" Paddle:	7 - 300 GPM ± 5% (1.6 - 68 m³/h)
Meter Capacity Range	
3" Standard:	3,750 - 63,750 gal (14 - 240 m³)
3" Extended:	18,750 - 318,750 gal (71 - 1,200 m³)
NXT:	1 - 9,900,000 gal (0 - 37,476 m³)
XT:	1,000 - 9,900,000 gal (3.8 - 37,476 m³)

DIMENSIONS

Distributor Pilot	3" O.D. (90 mm)
Drain Line	2" NPTF
Brine Valve 1800:	1"
Injector System	1800
Mounting Base	Top: 6" – 8 threaded, 6" flanged or welded flange
Height from Top of Tank	15" (381 mm)
Riser Tube Diameter	3" (76 mm)
Riser Height	Flush with top of tank

TYPICAL APPLICATIONS

Water Softener	24 - 63" diameter
Filter	24 - 42" diameter based on 10 GPM/ft²

ADDITIONAL INFORMATION

Electrical Rating	24/110/220V; 50/60 Hz
Estimated Shipping Weight	
Time Clock:	93 lbs
Metered Valve:	115 lbs
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature	
Cold Water Valve:	34 - 110°F (1 - 43°C)

*As defined in the U.S. EPA Safe Drinking Water Act; the product also meets California Proposition 65 Standards for lead-free brass.



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 WWW.PENTAIRAQUA.COM CUSTOMER CARE: 800.279.9404 tech-support@pentair.com

